Index

IEE Proceedings-B
Electric Power Applications
Vol. 140, 1993

ABBREVIATIONS

- p paper, address or lecture
- d discussion on a paper
- a abstract of paper or address
- e errata

Author index

A

Acarnley, P.P. Current measurement in three-phase brushless DC drives p71
Al-Bahrani, A.H., and Malik, N.H. Selection of the excitation capacitor for dynamic braking of induction machines p1
Al-Khoury, A.H.N., Stoll, R.L., and Bodner, B. see Stoll, R.L.
Allan, J., Hill, R.J., Carpenter, D.C., Mellitt, B., and Brown, J.C. see Hill, R.J.
Amaratunga, G.A.J., and Panda, S.K. see Panda, S.K.
Asher, G.M., and Sumner, M. see Sumner, M.

B

Bernot, F., Kauffmann, J.M., and Guichet, M.T. Computation of magnetic flux density and iron losses by Fourier-Bessel and Fourier-Laurent series in an electromagnetic vibration damper p18
Bhat, I., and Ojo, O. see Ojo, O.
Binns, K.J., Chaaban, F.B., and Hameed, A.A.K. Major design parameters of a solid canned permanent magnet motor with skewed magnets p161
Bodner, B., Stoll, R.L., and Al-Khoury, A.H.N. see Stoll, R.L.
Boldea, I., Fu, Z.X., and Nasar, S.A. High-performance reluctance generator p124
Bolton, H.R., and Chan, S. see Chan, S.
Bolton, H.R., and Chikwanda, H.S. see Chikwanda, H.S.
Boys, J.T. Theoretical spectra for narrow-band random PWM waveforms p393
Boys, J.T., Colby, R.S., and Otto, M.D. see Colby, R.S.
Brown, J.C., Hill, R.J., Carpenter, D.C., Mellitt, B., and Allan, J. see Hill, R.J.
Bumby, J.R., and Safi, S.K. see Safi, S.K.

C

Carpenter, D.C., Hill, R.J., Mellitt, B., Allan, J., and Brown, J.C. see Hill, R.J.
Chaaban, F.B., Binns, K.J., and Hameed, A.A.K. see Binns, K.J.
Chan, S., and Bolton, H.R. Performance enhancement of single-phase switched-reluctance motor by DC link voltage boosting p316
Chan, T.T., Chang, C.S., Ho, S.L., and Lee, K.K. see Chang, C.S.
Chandrasekaran, A., Sudha, S.A., and Rajagopalan, V. see Sudha, S.A.
Chang, C.S. AC train emergency fuzzy logic control using an event driven approach p307
Chang, C.S., Chan, T.T., Ho, S.L., and Lee, K.K. AI applications and solution techniques for AC-railway-system control and simulation p166
Chang, C.S., Ho, S.L., Chan, T.T., and Lee, K.K. Fast AC train emergency rescheduling using an event driven approach p281
Chen, Q., Lotfi, A.W., and Lee, F.C. see Lotfi, A.W.
Chen, T.-C., and Pan, C.-T. see Pan, C.-T.
Chen, T.H., Liaw, C.M., Chiang, S.J., Lee, C.M., and Wang, C.T. see Liaw, C.M.
Cheng, C.-P., and Liu, T.-H. see Liu, T.-H.
Chern, T.-L., and Wu, Y.-C. Design of brushless DC position servo systems using integral variable structure approach p27
Chiang, S.J., Liaw, C.M., Chen, T.H., Lee, C.M., and Wang, C.T. see Liaw, C.M.
Chikwanda, H.S., and Bolton, H.R. Analysis of the naturally commutated, convertor-fed induction motor drive system using a flux vector method p401
Cho, G.H., and Kwon, W.H. see Kwon, W.H.
Colby, R.S., Otto, M.D., and Boys, J.T. Analysis of LCI synchronous motor drives with finite DC link inductance p379
Čorda, J., Mašić, S., and Stephenson, J.M. Computation and experimental determination of running torque waveforms in switched-reluctance motors p387

D

De groot, D.J. Dimensional analysis of the linear induction motor p273
Ding, Z., and Hung, J.Y. see Hung, J.Y.

F

Finney, S.J., Green, T.C., and Williams, B.W. Review of resonant link topologies for inverters p103
Fu, Z.X., Boldea, I., and Nasar, S.A. see Boldea, I.
Funabiki, S., and Mechi, A. see Mechi, A.

G

Gowar, J., Williams, R., and Grant, D.A. see Williams, R.
Grant, D.A., Williams, R., and Gowar, J. see Williams, R.
Green, A.W. Modelling a push-pull parallel resonant convertor using generalised state-space averaging p350
Green, T.C., Finney, S.J., and Williams, B.W. see Finney, S.J.
Gufflet, D., and Malkin, P. Solid-state medium voltage contactor p147
Guichet, M.T., Bernot, F., and Kauffmann, J.M. see Bernot, F.

H

Hameed, A.A.K., Binns, K.J., and Chaaban, F.B. see Binns, K.J.
Haubrich, H.-J., and Machczyński, W. On simulation of the cathodic protection of extended buried conductor networks p337
Hill, R.J., Carpenter, D.C., Mellitt, B., Allan, J., and Brown, J.C. Correspondence: Calculation and measurement of rail impedances applicable to remote short-circuit fault currents p417
Ho, S.L., Chang, C.S., Chan, T.T., and Lee, K.K. see Chang, C.S.
Hung, J.Y., and Ding, Z. Design of currents to reduce torque ripple in brushless permanent magnet motors p260
Hunter, G.P., Ramsden, V.S., and Zhang, J. see Ramsden, V.S.

J

Jimin, Z., and Qishan, G. see Qishan, G.
Jutty, M.K., and Kazimierczuk, M.K. see Kazimierczuk, M.K.

K

Kauffmann, J.M., Bernot, F., and Guichet, M.T. see Bernot, F.
Kazimierczuk, M.K., and Jutty, M.K. Phase-modulated series–parallel resonant convertor with series load p297
Kazimierczuk, M.K., and Nandakumar, T. Class D voltage-switching inverter with tapped resonant inductor p177
Kostakis, G., and Manias, S.N. see Manias, S.N.
Kung, Y.S., Liaw, C.M., and Lin, F.J. see Liaw, C.M.
Kwon, W.H., and Cho, G.H. Analyses of static and dynamic characteristics of practical step-up nine-switch matrix convertor p139

L

Lee, C.M., Liaw, C.M., Chen, T.H., Chiang, S.J., and Wang, C.T. see Liaw, C.M.
Lee, F.C., Lotfi, A.W., and Chen, Q. see Lotfi, A.W.
Lee, K.K., Chang, C.S., Chan, T.T., and Ho, S.L. see Chang, C.S.
Lee, K.K., Chang, C.S., Ho, S.L., and Chan, T.T. see Chang, C.S.
Liaw, C.M., Chen, T.H., Chiang, S.J., Lee, C.M., and Wang, C.T. Small battery energy storage system p7
Liaw, C.M., Lin, F.J., and Kung, Y.S. Design and implementation of a high performance induction motor servo drive p241
Lin, F.J., Liaw, C.M., and Kung, Y.S. see Liaw, C.M.
Liu, T.-H., and Cheng, C.-P. Controller design for a sensorless permanent-magnet synchronous drive system p369
Lotfi, A.W., Chen, Q., and Lee, F.C. Nonlinear optimisation tool for the full-bridge zero-voltage-switched DC–DC convertor p289

M

Machczyński, W., and Haubrich, H.-J. see Haubrich, H.-J.
Malik, N.H., and Al-Bahrani, A.H. see Al-Bahrani, A.H.
Malkin, P., and Gufflet, D. see Gufflet, D.
Manias, S.N., and Kostakis, G. Modular DC–DC convertor for high-output voltage applications p97
Marchand, C., and Razek, A. Optimal torque operation of digitally controlled permanent magnet synchronous motor drives p232
Mašić, S., Čorda, J., and Stephenson, J.M. see Čorda, J.
Mechi, A., and Funabiki, S. Step-up/down voltage PWM AC to DC convertor with one switching device p35
Mecrow, B.C. Fully pitched-winding switched-reluctance and stepping-motor arrangements p61
Mellitt, B., Hill, R.J., Carpenter, D.C., Allan, J., and Brown, J.C. see Hill, R.J.
Miller, T.J.E., Staton, D.A., and Wood, S.E. see Staton, D.A.
Minari, Y., Shinohara, K., and Ueda, R. PWM-rectifier/voltage-source inverter without DC link components for induction motor drive p363
Mohamadein, A.L., Mostafa, A.S., and Rashad, E.M. see Mostafa, A.S.
Mostafa, A.S., Mohamadein, A.L., and Rashad, E.M. Analysis of series-connected wound-rotor self-excited induction generator p329
Mueller, M.A., and Williamson, S. see Williamson, S.

N

Nandakumar, T., and Kazimierczuk, M.K. see Kazimierczuk, M.K.
Nasar, S.A., Boldea, I., and Fu, Z.X. see Boldea, I.

O

Ojo, O., and Bhat, I. Steady-state and dynamic analyses of high-order parallel resonant convertors p209
Otto, M.D., Colby, R.S., and Boys, J.T. see Colby, R.S.

P

Pan, C.-T., and Chen, T.-C. Modelling and analysis of a three phase PWM AC–DC convertor without current sensor p201
Panda, S.K., and Amaratunga, G.A.J. Waveform detection technique for indirect rotor-position sensing of switched-reluctance motor drives. Part 2: Experimental results p89
Platt, D., and Smith, B.H. Twin rotor drive for an electric vehicle p131

Q

Qishan, G., and Jimin, Z. Saturated permeance of identically, doubly-slotted magnetic structures p323

R

Rahim, Y.H.A. Excitation of isolated three-phase induction generator by a single capacitor p44

Rajagopalan, V., Sudha, S.A., and Chandrasekaran, A. see Sudha, S.A.
Ramsden, V.S., Hunter, G.P., and Zhang, J. Performance and simulation of a single-phase-to-2-phase cycloconvertor motor drive p341
Rashad, E.M., Mostafa, A.S., and Mohamadein, A.L. see Mostafa, A.S.
Razek, A., and Marchand, C. see Marchand, C.

S

Safi, S.K., and Bumby, J.R. Design optimisation of a superconducting AC generator p267
Shinohara, K., Minari, Y., and Ueda, R. see Minari, Y.
Smith, B.H., and Platt, D. see Platt, D.
Staton, D.A., Miller, T.J.E., and Wood, S.E. Maximising the saliency ratio of the synchronous reluctance motor p249
Stephenson, J.M., Čorda, J., and Mališ, S. see Čorda, J.
Stoll, R.L., Bodner, B., and Al-Khoury, A.H.N. Method of magnetic sources applied to the basic configuration of a rotating electrical machine p217
Sudha, S.A., Chandrasekaran, A., and Rajagopalan, V. New approach to switch modelling in the analysis of power electronic systems p115
Sumner, M., and Asher, G.M. Autocommissioning for voltage-referenced voltage-fed vector-controlled induction motor drives p187

U

Ueda, R., Minari, Y., and Shinohara, K. see Minari, Y.

W

Wang, C.T., Liaw, C.M., Chen, T.H., Chiang, S.J., and Lee, C.M. see Liaw, C.M.
Williams, B.W., Finney, S.J., and Green, T.C. see Finney, S.J.
Williams, R., Grant, D.A., and Gowar, J. Multi-element transformers for switched-mode power supplies: toroidal designs p152
Williams, R., Grant, D.A., and Gowar, J. Use of multielement transformers in quasiresonant convertors p357
Williamson, S., and Mueller, M.A. Calculation of the impedance of rotor cage end rings p51
Wood, S.E., Staton, D.A., and Miller, T.J.E. see Staton, D.A.
Wu, Y.-C., and Chern, T.-L. see Chern, T.-L.

Z

Zhang, J., Ramsden, V.S., and Hunter, G.P. see Ramsden, V.S.

Subject index

ACOUSTOELECTRIC EFFECTS

Theoretical spectra for narrow-band random PWM waveforms. J.T. Boys p393

CIRCUIT THEORY AND DESIGN

Performance enhancement of single-phase switched-reluctance motor by DC link voltage boosting. S. Chan and H.R. Bolton p316

COMPUTER SIMULATION

On simulation of the cathodic protection of extended buried conductor networks. H.-J. Haubrich and W. Machczyński p337

CONTROL EQUIPMENT AND APPLICATIONS

Controller design for a sensorless permanent-magnet synchronous drive system. T.-H. Liu and C.-P. Cheng p369

CONVERTORS

Modelling a push–pull parallel resonant convertor using generalised state-space averaging. A.W. Green p350
Modelling and analysis of a three phase PWM AC–DC convertor without current sensor. C.-T. Pan and T.-C. Chen p201
Modular DC–DC convertor for high-output voltage applications. S.N. Manias and G. Kostakis p97
Nonlinear optimisation tool for the full-bridge zero-voltage-switched DC–DC convertor. A.W. Lotfi, Q. Chen and F.C. Lee p289
Phase-modulated series–parallel resonant convertor with series load. M.K. Kazimierczuk and M.K. Jutty p297
Steady-state and dynamic analyses of high-order parallel resonant convertors. O. Ojo and I. Bhat p209
Step-up/down voltage PWM AC to DC convertor with one switching device. A. Mechi and S. Funabiki p35
Use of multielement transformers in quasiresonant convertors. R. Williams, D.A. Grant and J. Gowar p357

ELECTRICAL MACHINES

Method of magnetic sources applied to the basic configuration of a rotating electrical machine. R.L. Stoll, B. Bodner and A.H.N. Al-Khoury p217
Twin rotor drive for an electric vehicle. D. Platt and B.H. Smith p131

ELECTROMAGNETIC THEORY

Computation of magnetic flux density and iron losses by Fourier-Bessel and Fourier-Laurent series in an electromagnetic vibration damper. F. Bernot, J.M. Kauffmann and M.T. Guichet p18

GENERATORS

Analysis of series-connected wound-rotor self-excited induction generator. A.S. Mostafa, A.L. Mohamadein and E.M. Rashad p329
Design optimisation of a superconducting AC generator. S.K. Safi and J.R. Bumby p267
Excitation of isolated three-phase induction generator by a single capacitor. Y.H.A. Rahim p44
High-performance reluctance generator. I. Boldea, Z.X. Fu and S.A. Nasar p124

INDUCTION MOTORS

Analysis of series-connected wound-rotor self-excited induction generator. A.S. Mostafa, A.L. Mohamadein and E.M. Rashad p329
Analysis of the naturally commutated, convertor-fed induction motor drive system using a flux vector method. H.S. Chikwanda and H.R. Bolton p401
Autocommissioning for voltage-referenced voltage-fed vector-controlled induction motor drives. M. Sumner and G.M. Asher p187
Calculation of the impedance of rotor cage end rings. S. Williamson and M.A. Mueller p51
Design and implementation of a high performance induction motor servo drive. C.M. Liaw, F.J. Lin and Y.S. Kung p241
Excitation of isolated three-phase induction generator by a single capacitor. Y.H.A. Rahim p44
PWM-rectifier/voltage-source inverter without DC link components for induction motor drive. Y. Minari, K. Shinohara and R. Ueda p363
Performance and simulation of a single-phase-to-2-phase cycloconvertor motor drive. V.S. Ramsden, G.P. Hunter and J. Zhang p341
Selection of the excitation capacitor for dynamic braking of induction machines. A.H. Al-Bahrani and N.H. Malik p1

LINEAR MOTORS

Dimensional analysis of the linear induction motor. D.J. de Groot p273

MAGNETIC DEVICES AND PROPERTIES

Major design parameters of a solid canned permanent magnet motor with skewed magnets. K.J. Binns, F.B. Chaaban and A.A.K. Hameed p161
Saturated permeance of identically, doubly-slotted magnetic structures. G. Qishan and Z. Jimin p323

MATHEMATICAL TECHNIQUES

Fast AC train emergency rescheduling using an event driven approach. C.S. Chang, S.L. Ho, T.T. Chan and K.K. Lee p281
Modelling a push–pull parallel resonant convertor using generalised state-space averaging. A.W. Green p350

MOTORS

Design of brushless DC position servo systems using integral variable structure approach. T.-L. Chern and Y.-C. Wu p27
Design of currents to reduce torque ripple in brushless permanent magnet motors. J.Y. Hung and Z. Ding p260

NETWORKS

On simulation of the cathodic protection of extended buried conductor networks. H.-J. Haubrich and W. Machczyński p337

POWER ELECTRONICS

Analysis of LCI synchronous motor drives with finite DC link inductance. R.S. Colby, M.D. Otto and J.T. Boys p379
Class D voltage-switching inverter with tapped resonant inductor. M.K. Kazimierczuk and T. Nandakumar p177
New approach to switch modelling in the analysis of power electronic systems. S.A. Sudha, A. Chandrasekaran and V. Rajagopalan p115
PWM-rectifier/voltage-source inverter without DC link components for induction motor drive. Y. Minari, K. Shinohara and R. Ueda p363
Review of resonant link topologies for inverters. S.J. Finney, T.C. Green and B.W. Williams p103
Solid-state medium voltage contactor. D. Gufflet and P. Malkin p147
Theoretical spectra for narrow-band random PWM waveforms. J.T. Boys p393

POWER SYSTEM PROTECTION

Small battery energy storage system. C.M. Liaw, T.H. Chen, S.J. Chiang, C.M. Lee and C.T. Wang p7

POWER SYSTEMS AND PLANT

Small battery energy storage system. C.M. Liaw, T.H. Chen, S.J. Chiang, C.M. Lee and C.T. Wang p7

RAILWAY ELECTRIFICATION AND TRANSPORTATION

AC train emergency fuzzy logic control using an event driven approach. C.S. Chang p307
AI applications and solution techniques for AC-railway-system control and simulation. C.S. Chang, T.T. Chan, S.L. Ho and K.K. Lee p166

RELUCTANCE MOTORS

Computation and experimental determination of running torque waveforms in switched-reluctance motors. J. Corda, S. Mašič and J.M. Stephenson p387
Fully pitched-winding switched-reluctance and stepping-motor arrangements. B.C. Mecrow p61
Performance enhancement of single-phase switched-reluctance motor by DC link voltage boosting. S. Chan and H.R. Bolton p316
Waveform detection technique for indirect rotor-position sensing of switched-reluctance motor drives. Part 2: Experimental results. S.K. Panda and G.A.J. Amaratunga p89

SERVOMOTORS

Controller design for a sensorless permanent-magnet synchronous drive system. T.-H. Liu and C.-P. Cheng p369
Current measurement in three-phase brushless DC drives. P.P. Acarnley p71

SIMULATION

Calculation of the impedance of rotor cage end rings. S. Williamson and M.A. Mueller p51
Design of brushless DC position servo systems using integral variable structure approach. T.-L. Chern and Y.-C. Wu p27
Fast AC train emergency rescheduling using an event driven approach. C.S. Chang, S.L. Ho, T.T. Chan and K.K. Lee p281
Modelling a push–pull parallel resonant convertor using generalised state-space averaging. A.W. Green p350
Modelling and analysis of a three phase PWM AC–DC convertor without current sensor. C.-T. Pan and T.-C. Chen p201
New approach to switch modelling in the analysis of power electronic systems. S.A. Sudha, A. Chandrasekaran and V. Rajagopalan p115

STEPPING MOTORS

Saturated permeance of identically, doubly-slotted magnetic structures. G. Qishan and Z. Jimin p323

SUPERCONDUCTIVITY

Design optimisation of a superconducting AC generator. S.K. Safi and J.R. Bumby p267

SYNCHRONOUS MOTORS

Controller design for a sensorless permanent-magnet synchronous drive system. T.-H. Liu and C.-P. Cheng p369
Major design parameters of a solid canned permanent magnet motor with skewed magnets. K.J. Binns, F.B. Chaaban and A.A.K. Hameed p161
Maximising the saliency ratio of the synchronous reluctance motor. D.A. Staton, T.J.E. Miller and S.E. Wood p249
Optimal torque operation of digitally controlled permanent magnet synchronous motor drives. C. Marchand and A. Razek p232

THYRISTORS

Solid-state medium voltage contactor. D. Gufflet and P. Malkin p147

TRANSFORMERS

Analyses of static and dynamic characteristics of practical step-up nine-switch matrix convertor. W.H. Kwon and G.H. Cho p139
Modular DC–DC convertor for high-output voltage applications. S.N. Manias and G. Kostakis p97
Multielement transformers for switched-mode power supplies: toroidal designs. R. Williams, D.A. Grant and J. Gowar p152
Theoretical spectra for narrow-band random PWM waveforms. J.T. Boys p393
Use of multielement transformers in quasiresonant convertors. R. Williams, D.A. Grant and J. Gowar p357